



“Make your machine more employable / profitable with the GMT 050 FG felling grapple”

FELLING GRAPPLE GMT 050 FG



NEW

The felling grapple GMT 050 FG can be used by any machine that can handle a normal wood grapple. All this without having to do any technical modifications.

Because of the patented valve block, there is no need for extra hydraulic lines and / or electric cables.

The felling grapple GMT 050 FG has the following benefits:

- Enlarge the employability of your machine
- Fast cycle of operation, so usable near roads, railroads and in (public)parks
- Save up to 60% of man-hours
- Thanks to the saw cut there is no damage on the stem or tree trunk
- Remove or prune / shear / cut trees safely and efficiently





“A safe and efficient way for removing and pruning trees”

FELLING GRAPPLE GMT 050 FG

Technical details

Sizes

Max opening grapple	1220 mm
Max width with open grapple	1375 mm
Min width with closed grapple	930 mm
Height at saw position	750 mm
Height at load position	630 mm
Weight	385 kg

Hydraulics

Minimum oil flow	60 / 100 ltr
Working pressure	180 / 250 bar

Saw

Length sawing blade	640 mm
Sawing chain	2 mm 404" 74 links
Max felling diameter	500 mm
Chain oil tank capacity	2 ltr
Sawmotor	10 cc



Gierkink Machine Techniek BV

Kapelweg 44

7134 RJ Vragender

the Netherlands

Tel +31 544 - 370315

Fax +31 544 - 370316

www.gierkinkmt.nl

info@gierkinkmt.nl