



# SuperGrip -RS

## Features

- Extra heavily reinforced model for the toughest jobs in the forest and excavator applications
- Tapered sleeve pin design eliminates any joint motion
- Strong casted push rod
- 1000 hour greasing interval
- Strong cushioned cylinder reduces shock loads, designed for up to 25 MPa working pressure
- Grapple saw option available on all models

SuperGrip		260RS	300RS	360RS
Weight	kg	269	272	410
Max. load	kg	4 500	4500	8 000
Gripping area, tip-tip	m <sup>2</sup>	0.26	0.30	0.36
Gripping area, practical	m <sup>2</sup>	0.30	0.35	0.42
Max. gripping width "A"	mm	1 496	1 479	1 822
Overall grapple width "B"	mm	434	434	522
Height, arms tip-tip "C"	mm	874	910	997
Max. height arms open	mm	788	836	853
Min. height arms closed	mm	560	560	656
Grapple jaw width	mm	424	424	484
Min. gripping diameter	mm	93	91	108
Gripping force, arms open, at 25 MPa	kN	10.9	10.4	18.5
Gripping force, arms tip-tip, at 25 MPa	kN	15.1	14.6	19.2
Opening time, at 50 l/min	s	0.9	0.9	1.6
Closing time, at 50 l/min	s	1.7	1.7	2.6
Max. operating pressure	MPa	25	25	25