



## SuperSaw 555S, -555S HD

### Features

- Designed for optimal balance.
- Automatic chain tensioning and proportional chain lubrication.
- Fast and easy bar and chain replacement.
- SuperCut minimizes down time and increases productivity.
- Built in bar feed cylinder.
- Integrated mounting of saw motor.
- Pressure feed out system for optimized saw performance.
- Simple adjustment of bar feed pressure.
- Simple installation on forwarder and truck (SS555S) and excavator (SS555S HD).

		555S	555S HD
<b>Saw motor displacement</b>	<b>cm<sup>3</sup></b>	19	19
<b>Weight</b>	<b>kg</b>	195	235
<b>Length "A"</b>	<b>mm</b>	1168	1168
<b>Width "B"</b>	<b>mm</b>	376	434
<b>Height "C"</b>	<b>mm</b>	465	465
<b>Width "D"</b>	<b>mm</b>	148	148
<b>Min. hydraulic pressure, saw motor</b>	<b>MPa</b>	16	16
<b>Min. hydraulic flow, saw motor</b>	<b>l/min</b>	110	110
<b>Max. saw chain speed</b>		See recommendations from each saw chain manufacturer	
<b>Max. power input to saw chain</b>		See recommendations from each saw chain manufacturer	
<b>Saw chain</b>		.404"	.404"
<b>Saw bar</b>	<b>cm</b>	90	90
<b>Recommended grapples 555S</b>		SGII 360S, SGII 420S and SG 360S, SG 520S	
<b>Recommended grapples 555S HD</b>		SG360S and SG520S	